

Area sq.mm. (1)	E (2)	E (3)	A (4)	C (5)	D (6)	F (7)	B (8)	H (9)	G (10)	J (11)	Cat No.
2.5	3.2	-	1.9-2.1	5.4-5.6	6.3-6.9	3.3-3.7	7	4	4	18	RASS-164
2.5	3.2	3.7	2.5-2.7	5.4-5.6	6.7-7.3	2.7-3.1	7	4	4	18	RASS-165
4	3.2	4.2	2.8-3.0	5.4-5.6	6.9-7.5	2.4-2.8	7	4	4	18	RASS-166
6	3.2	5.2	3.4-3.6	5.4-5.6	7.2-7.8	1.8-2.2	7	7	6	24	RASS-168
10	4.2	5.2	3.7-3.9	6.1-6.3	8.1-8.7	2.2-2.6	7	9	8	28	RASS-170
10	4.2	6.4	4.3-4.5	7.1-7.3	9.4-10.9	2.6-3.0	9	9	8	30	RASS-171
16	5.2	8.2	5.3-5.5	8.2-8.4	11.1-11.7	2.7-3.1	13	11	9	37	RASS-173
25	6.4	10.2	6.8-7.1	9.6-9.8	13.4-14.0	2.5-2.9	16	11	10	44	RASS-176
35	6.4	10.2	7.8-8.1	10.7-10.9	15.1-15.7	2.6-3.0	18	11	11	47	RASS-180
50	6.4	10.2	9.1-9.4	12.9-13.11	8.0-18.6	3.4-4.0	22	13	11	54	RASS-183
70	8.2	12.7	11.1-11.4	15.4-15.6	21.7-22.3	3.9-4.5	26	13	13	60	RASS-186
95	10.2	12.7	13.0-13.3	17.3-17.5	24.6-25.2	3.9-4.5	28	14	14	64	RASS-189
120	10.2	16.2	14.5-14.9	19.5-19.7	27.7-38.3	4.5-5.1	32	15	15	73	RASS-192
150	10.2	16.2	16.2-16.6	21.4-21.6	30.6-31.2	4.7-5.3	34	17	17	79	RASS-195
185	10.2	16.3	18.2-18.6	23.9-24.1	34.2-35.0	5.0-6.0	36	18	18	84	RASS-200
240	12.7	20.3	20.7-21.3	27.9-28.2	39.6-40.6	6.3-7.3	44	22	22	102	RASS-202
300	16.2	20.3	23.5-24.1	30.9-31.2	44.2-45.2	6.5-7.5	47	27	27	115	RASS-204
400	16.2	20.3	26.5-27.1	35.4-35.7	50.5-51.5	7.8-9.2	56	31	30	130	RASS-206
500	20.3	-	29.5-30.2	40.9-41.2	57.4-58.8	10.1-11.9	60	33	32	140	RASS-207
630	20.3	-	34.5-35.2	45.9-46.2	65.4-66.0	10.1-11.9	59	35	34	154	RASS-208
800	-	-	38.5-39.2	50.9-51.2	72.5-74.1	11.1-12.9	77	39	39	180	RASS-209
1000	-	-	43.0-43.7	56.8-57.2	80.9-82.9	12.5-14.5	100	45	45	220	RASS-210

Dimension : as per IS 8309 1993

All dimensions are in mm.

Conductivity : above 60% IACS