

| Area<br>sq.mm. | ±0.12<br>øE | +0.3-0.0<br>øA | ±0.2<br>øC | ±0.5<br>D | ±0.5<br>F | +3-0<br>B | ±0.5<br>K | ±0.5<br>H | ±0.5<br>G | ±0.5<br>J | Ratan's<br>Cat No. |
|----------------|-------------|----------------|------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|--------------------|
| 16             | 8.4         | 5.4            | 7.4        | 11.0      | 2.0       | 14        | 5         | 9         | 9         | 37        | RXLS-16            |
| 25             | 8.4         | 7.2            | 9.6        | 14.0      | 2.4       | 41        | 7         | 12        | 9         | 69        | RXLS-25            |
| 35             | 10.5        | 8.3            | 11.1       | 16.0      | 2.8       | 50        | 7         | 11        | 11        | 79        | RXLS-35            |
| 50             | 10.5        | 10.1           | 13.5       | 19.5      | 3.4       | 49        | 8         | 13        | 11        | 81        | RXLS-50            |
| 70             | 13.0        | 10.2           | 14.5       | 20.5      | 4.3       | 62        | 8         | 13        | 13        | 96        | RXLS-70            |
| 95             | 13.0        | 12.0           | 16.9       | 23.5      | 4.9       | 73        | 8         | 14        | 14        | 109       | RXLS-95            |
| 120            | 13.0        | 13.7           | 19.0       | 26.5      | 5.3       | 73        | 11        | 15        | 15        | 114       | RXLS-120           |
| 150            | 13.0        | 15.1           | 21.1       | 29.5      | 6.0       | 83        | 11        | 17        | 17        | 128       | RXLS-150/1         |
| 150            | 17.0        | 15.1           | 21.1       | 29.5      | 6.0       | 83        | 11        | 17        | 17        | 128       | RXLS-150/2         |
| 185            | 17.0        | 16.6           | 23.9       | 33.0      | 4.3       | 83        | 12        | 18        | 18        | 131       | RXLS-185           |
| 225            | 17.0        | 18.6           | 26.1       | 36.0      | 7.5       | 86        | 14        | 20        | 20        | 140       | RXLS-225           |
| 240            | 17.0        | 19.3           | 27.2       | 37.5      | 7.9       | 86        | 14        | 22        | 22        | 144       | RXLS-240           |
| 300            | 17.0        | 21.8           | 30.2       | 42.0      | 8.4       | 89        | 14        | 27        | 27        | 157       | RXLS-20/1          |
| 300            | 20.0        | 21.8           | 30.2       | 42.0      | 8.4       | 89        | 14        | 27        | 27        | 157       | RXLS-20/2          |
| 400            | 17.0        | 25.0           | 34.8       | 48.0      | 9.8       | 113       | 13        | 30        | 30        | 186       | RXLS-400           |
| 500            | 17.0        | 28.2           | 39.1       | 54.0      | 10.9      | 125       | 15        | 32        | 32        | 204       | RXLS-500           |
| 630            | 17.0        | 31.7           | 44.4       | 61.0      | 12.7      | 146       | 16        | 34        | 34        | 224       | RXLS-630           |
| 800            | 20.3        | 35.7           | 49.5       | 68.0      | 13.8      | 147       | 25        | 39        | 39        | 250       | RXLS-800           |
| 1000           | 20.3        | 41.0           | 56.0       | 77.5      | 15.0      | 160       | 30        | 45        | 45        | 280       | RXLS-1000          |

All dimensions are in mm.

Conductivity : above 60% IACS